Ancient TL

www.ancienttl.org · ISSN: 2693-0935

Jain, M., Bøtter-Jensen, L., Murray, A., Denby, P., Tsukamoto, S. and Gibling, M., 2005. *Revisiting TL: Dose measurement beyond the OSL range using SAR.* Ancient TL 23(1): 9-24. https://doi.org/10.26034/la.atl.2005.381

This article is published under a *Creative Commons Attribution 4.0 International* (CC BY): https://creativecommons.org/licenses/by/4.0



© The Author(s), 2005

Revisiting TL: Dose measurement beyond the OSL range using SAR

M. Jain^{1*}, L. Bøtter-Jensen¹, A.S. Murray², P.M. Denby¹, S. Tsukamoto³ and M.R. Gibling⁴

(*Corresponding author mayank.jain@risoe.dk)

(Received 3 May 2005; in final form 25 May 2005)

Abstract

We show here that isothermal TL (ITL) at 310 and 320°C can be used to extend the luminescence dating range in quartz. These signals have markedly different behaviour than the OSL signal with respect to dose response and bleaching efficiency using blue light; this suggests that the 325°C TL peak, from which these signals are likely to be derived, perhaps, consists of traps with very different optical depths and saturation characteristics.

The feldspar IRSL signal (blue emission) shows significant dose under-estimation on account of fading. This problem is partly circumvented by measurements using blue ITL at 310°C. The red ITL signal at 310°C does not show dose underestimates. A firm conclusion as to whether this signal fades or not can, however, only be made with a better understanding of sensitivity changes during the red ITL measurement of the natural signal. Both blue and red ITL signals in feldspars perhaps use the same trap. The fading and/or sensitivity changes, therefore, relate to the recombination centre.

On account of the high dose at which saturation appears, the ITL signal from quartz at 310 and 320°C is the best candidate for extending the dose range up to 1.4 kGy in samples from the southern Indo-Gangetic plains.

Keywords

Isothermal TL, Red emission, Quartz, Feldspars, Fading, Indo-Gangetic plains

Introduction

optically the last decade stimulated Over luminescence (OSL) dating of quartz has been established as a robust sediment dating method (Murray and Olley, 2002). This method relies on measurement of a light sensitive signal generally referred to as the fast OSL component. Unfortunately an early saturation of the signal responsible for the fast component limits the OSL dating range using quartz. Nevertheless, because of the greater likelihood that this signal was zeroed during sediment transport, under either sub-aerial and sub-aqueous conditions, the OSL signal is more likely to provide accurate sedimentation age than thermoluminescence (TL) signal.

In our experience many samples from the Indian subcontinent give a quartz OSL signal which saturates at about 100 - 150 Gy. Combined with dose rates of ~ 3 - 5 Gy/ka, this gives an OSL dating limit of about 20-50 ka. This dating limit greatly restricts investigations of the climate and tectonic changes that have shaped the Indian sub-continent during the Late Quaternary. A good example is the difficulty in dating the large sediment pile in the Himalayan foreland basin, commonly referred to as the Indo-Gangetic plains. This constitutes an excellent archive of the influence of climate, tectonism and sea level changes on one of the worlds largest and most dynamic river systems, but this archive cannot be interpreted without a chronological framework.

¹ Risø National Laboratory, DK-4000 Roskilde, Denmark.

² Nordic Laboratory for Luminescence Dating, Department of Earth Sciences, Århus University, Risø National Laboratory, DK-4000 Roskilde, Denmark

³ Department of Geography, Tokyo Metropolitan University, Hachioji, Tokyo 192-0397, Japan

⁴ Department of Earth Sciences, Dalhousie University, Halifax, Nova Scotia, B3H 3J5, Canada

One way of breaking this age barrier is to explore quartz signals other than the fast OSL component. Alternatively, one can make use of luminescence signals from feldspar if due allowance for signal fading is made (Huntley and Lamothe, 2001). An important aspect of any new approach should be the ability to measure dose using a single small subsample (aliquot) so that by making several such measurements one can obtain a precise estimate of equivalent dose as well as an assessment of bleaching. Previously reported approaches to extending the age range include:

(i) Quartz

The slowly decaying OSL signal in quartz saturates above 1 kGy (Singarayer and Bailey, 2003). However, the rate of decay when stimulated using blue light ($470\Delta30$ nm) is very low; this causes a poor signal-to-noise ratio. Also rather long times (several ks) are required to empty the luminescence signal during the measurement. Owing to these constraints a routine dating method using the slow OSL component is not yet practical.

Two important quartz TL dating signals, from the so called 325 and 375°C peaks, have been identified (Aitken 1985). Previous attempts to use the 325°C peak have been based on a comparison of bleached and unbleached TL peaks (e.g. Franklin and Hornyak, 1990). It has been shown earlier that doseresponse curves using the 325°C TL signal have a significantly higher saturation level than the OSL signal (Figure 6a in Jain et al., 2005); in these samples from the Thar Desert the apparent dose saturation levels in multiple-aliquot growth curves were about 200 Gy for the OSL signal and about 450 Gy for the 325°C TL signal. There are also examples of measured quartz TL doses of up to 400 Gy from the coastal dune succession of southeast Australia (Huntley and Prescott, 2001). In general, however, a large scatter in the multiple aliquot data renders it difficult to make a direct, meaningful comparison of the TL and OSL saturation characteristics. In fact the differences in the dose saturation levels are generally hidden under the scatter in the data. Regarding the 375°C TL peak, Murray and Wintle (2000a) developed a single-aliquot regenerative-dose method using the isothermal TL (ITL) signal at 340°C. There was, however, only a limited improvement in the saturation level compared to the OSL and the residual levels in modern samples were high.

A completely different TL signal with emission in the 600-640 nm band can potentially extend the age range as it has very high saturation levels (> 20 kGy). However, this signal is strongest in volcanic quartz

(Fattahi and Stokes, 2000), and generally weak in quartz of plutonic origin.

ii) Feldspars

The dose saturation level in feldspars is generally acknowledged to be greater than that in quartz (e.g. Wallinga et al., 2001). However, because of the signal fading demonstrated in many samples (Huntley and Lamothe, 2001) the accuracy of feldspar ages is very dependent on how well one can correct for the age underestimation. These fading corrections are either model dependent or based on independent age control. In order to tackle fading, different emission signals from feldspars have been examined. For example, it has been suggested that the red emission from feldspars shows little or no fading (Zink and Visocekas, 1997; Fattahi and Stokes, 2003).

In general there have been few systematic investigations into the use of the TL signal using a single aliquot method (for example, Murray and Wintle, 2000a). An important reason for this is a shift in thrust to OSL dating in the last decade or so. Although, it is well known that TL is not as sensitive to daylight as the fast OSL signal, TL can potentially be used for dating old samples where burial doses are likely to be much greater than any residual doses. If dose saturation levels are high (>500 Gy) then these TL signals can potentially be used for dating beyond the OSL age range. In this contribution we test the use of ITL signals on single aliquots of quartz and feldspars for extending the age range. In particular, we present new results on the UV ITL emission from quartz and red ITL emission from feldspar.

Experimental details

Samples reported in this study were collected from exposed river sections in the southern Indo-Gangetic plains (Gibling et al., 2005). The main sediment sources are from the Himalayas. However, southern cratonic contributions are also significant. Thus one expects a mixture of granitic and metamorphosed quartz and feldspars in these samples.

Coarse grains of quartz ($60-105~\mu m$) were extracted from various sediment samples by routine treatment employing 10% hydrochloric acid (HCl) followed by sieving and 60 minutes of hydrofluoric acid (HF). The purity of the quartz extracts was confirmed using IR stimulation after a regeneration dose. The mixed sample from immediately prior to the HF treatment was considered as a feldspar sample. Although this mixture consists of quartz and feldspars, it can be effectively considered to give only feldspar luminescence signal; this is because there was no detectable signal from pure quartz aliquots in both

IRSL and red isothermal TL, and in the blue isothermal TL the quartz signal comprised <0.5% of the signal from the quartz and feldspar mixture. No attempt was made to separate various feldspar minerals. The results reported here are, therefore, based on mixed feldspar mineralogy.

An automated Risø TL/OSL reader (TL/OSL-DA-15) (Bøtter-Jensen et al., 2002) was used for all measurements. Blue light stimulation used an array of 28 LEDs (470 Δ 30 nm) delivering \sim 50 mW.cm⁻² at the sample position after passing through GG-420 filters. IR stimulation used an IR laser (830 Δ 10 nm) with a stimulation intensity of \sim 400 mW.cm⁻². Laboratory irradiations were made using calibrated 90 Sr/ 90 Y beta sources delivering about 0.10 or 0.34 Gy/s to quartz.

A heating rate of 2°C/s, unless otherwise mentioned, was used during the preheat and thermoluminescence measurements. Detection optics comprised U-340 (~99% transmission between 260 and 390 nm) filters for all quartz measurements, and a combination of BG-39 and 7-59 filters for the blue emission measurements from feldspars, both detected by an EMI 9635Q bialkali photomultiplier tube. The red emission from feldspars was measured using a combination of Comar 650IU (650±20 nm) and 650IW (650±37 nm) detection filters in front of a red sensitive GaAs photomultiplier tube (Hamamatsu R943-02) which is cooled externally by a Photocool series PMT housing (Model PC182CE).

Elemental concentrations of Uranium, Thorium and Potassium were determined using high resolution gamma spectrometry for calculation of dose rates (Murray et al., 1987).

Results and discussion

We describe below the experiments and dosimetric results from both quartz and feldspar extracts from the studied samples. Quartz results are based on OSL and isothermal TL (ITL) measurements, while those on feldspars are based on infrared stimulated luminescence (IRSL, blue emission) and ITL (blue or red emissions) measurements.

Quartz OSL and Feldspar IRSL

The single-aliquot regenerative-dose (SAR) procedure (Murray and Wintle, 2000b) was used for quartz extracts. The signal was measured using blue light stimulation at an elevated temperature of 125°C

for 40s following a preheat of 260°C for 10s or a cutheat to 260°C. The size of the test dose was 5 Gy. OSL characteristics for sample K-IX/49 are shown in Figure 1. The OSL signal was dominated by the fast component (Figure 1a). The natural signal was in apparent charge saturation, observed to be ~150 Gy (Figure 1b). Thus the sample was beyond the OSL dating range. The growth curve was fitted using an equation of the form $L=L_0(1-\exp-D/D_0)$ where L is the sensitivity corrected luminescence output to a given dose D, and Lo and Do are constants. The average D₀ value (this defines the curvature of the growth curve) from various aliquots of the sample was calculated to be 65 Gy suggesting that the maximum measurable dose may be about 130 Gy (at twice the D₀ value, or 15% below the saturation intensity).

Although most samples were in the OSL saturation range, we also measured some younger samples on which OSL ages could be determined (Table 1). An OSL dose recovery test was carried out to confirm that a given dose on a previously unheated sample can be accurately measured in the laboratory. For SNG-1 the dose recovery (recovered/given dose) was 0.98±0.01 (n= 10) for a given dose of 15.6 Gy. For sample BTH-II/8 the dose recovery ratio was 0.95±0.02 (n=6) for a given dose of 104 Gy. These dose recovery tests suggest that there are no significant laboratory artefacts which may cause possible offsets in equivalent dose estimates. On two samples SNG-1 and BTH-II/8 the quartz ages were confirmed by AMS radiocarbon ages on carbonate shells (details in Gibling et al., 2005).

Feldspar extracts from different samples were measured using IR stimulated luminescence (in blue detection). Identical cutheat and preheat treatments, involving TL to 300° C, were carried out after various regeneration doses and a test dose of 17 Gy. Considering that the samples are old, these heat treatments were employed with an aim of sampling only the thermally stable fraction of the feldspar IRSL signal. IR stimulation was carried out at 125° C for 80s which reduced the signal to background level (Figure 1c). The natural luminescence signal was below the saturation level (average $D_0 = 173$ Gy) in all the samples (Figure 1d).




Figure 1: a) Natural OSL decay curve from a quartz aliquot of sample K-IX/49. The inset shows a pseudo LM-OSL curve derived from the same data. b) Dose response curve for the same aliquot of quartz. c) Natural IRSL decay curve from a feldspar aliquot of sample K-IX/49. The inset shows a pseudo LM-IRSL curve. d) Dose response curve for the same feldspar aliquot. The first 0.8s was used for signal integration in both IRSL and OSL decay curves.

A comparison of quartz OSL and feldspar IRSL ages on the five samples that were measurable by both the methods is shown in Figure 2. Feldspar doses are on average 40% lower than those from quartz; these dose differences will translate to about 50% age under-estimation when the additional internal dose rate in feldspars is taken into account (discussed




Figure 2: A comparison of dose estimates derived using Quartz OSL (UV emission) and Feldspar IRSL (blue emission).

later). We attribute this under-estimation to fading, although, some differences might also occur because of errors in our dose estimation using SAR on feldspars (e.g. Wallinga et al., 2001). Since the dose underestimation is clearly systematic, it may be possible to correct for dose in older feldspar samples using a calibration based on quartz. However, in the absence of any known age older samples it is difficult to test whether such an extrapolation is meaningful or not.

Thermoluminescence

Results on TL investigations on quartz and feldspars are discussed below.

Quartz: Luminescence characteristics and equivalent dose

A TL curve obtained after a laboratory dose of 34 Gy and a preheat of 260°C for 10s is shown in Figure 3a; this curve was measured using an aliquot of the modern sample Bth (0). The curve shows a broad TL peak between 300 and 500°C. Even after heating to 500°C the composite peak is not emptied completely.

Sample Env.		Quartz D_e (Gy) OSL ITL	Feldspar D _e (Gy) Red ITL Blue ITL	r D_e (Gy) Blue IT∟	IRSL	Dose rate (Gy/ka) Quartz Feldspar	ate (Gy/ka) Feldspar	Age (ka) Quartz OSL	Quartz (ITL)	Feld (red ITL)
K-II/2B F		228 ± 4	337 ± 16	273 ± 9	170 ± 7	1.0	3.3 ± 0.2		78±4	101 ± 9
		232 ± 9		241 ± 9	181 ± 7	0.3	5.4 ± 0.4		47 ± 3	8 + 8
	136 ± 13	138 ± 7		122 ± 7	82 ± 3	0.2	4.3 ± 0.3	35 ± 4	36 ± 3	44 ± 5
		203 ± 2		252 ± 4	227 ± 36	0.5	4.0 ± 0.6		57 ± 8	102 ± 17
	113 ± 4	85 ± 2		70 ± 0	56 ± 2	0.3	4.9 ± 0.4	+I	19 ± 1	18 ± 2
	130 ± 4	133 ± 5		109 ± 2	86 ± 4	0.3	5.1 ± 0.4	28 ± 2	28 ± 2	38 ± 4
	103 ± 3	69 ± 3		51±2	50 ± 2	0.2	4.3 ± 0.3	+1	18±1	19 ± 2
SNG-1 F	48±3	59 ± 3		45±1	33 ± 1	3.9 ± 0.2	4.3 ± 0.3	12±1	15±1	19±2
	42 ±1	34 ± 1		21 ± 1	22 ± 1	0.2	3.2 ± 0.3	15±1	12 ± 1	10 ± 1
		418 ± 35		38	325 ± 22	0.2	4.0 ± 0.3		117 ± 11	
		ΣZ		10	150 ± 11	0.2	3.9 ± 0.3			
		286 ± 11			ΣZ	0.2	3.9 ± 0.3		82 ± 6	86 ± 9
		216 ± 5			ΣZ	3.2 ± 0.2	3.6 ± 0.3		67 ± 4	109 ± 10
		106 ± 9			ΣZ	± 0.2	3.9 ± 0.3		31±3	
	36 ± 3	31 ± 1			ΣZ	3.1 ± 0.2	3.5 ± 0.3	11 ± 1	10 ± 1	

 $\label{eq:NM-not measured} NM-not measured \\ Sat.-signal in saturation \\ Env-Depositional environment (F-fluvial, A-Aeolian) \\$

Table 1: Summary of Luminescence dating results from the samples collected from the southern Indo-Gangetic plains.




Figure 3: a) TL peak of an aliquot of quartz from a modern sample (BTh0) after a dose of 34 Gy and a preheat of 260°C for 10s. TL was measured at the rate of 5°C/s. The dotted curve is the repeat TL run after the TL signal had been measured. b) Natural isothermal TL decay curves measured at different temperatures c) same data plotted as peak transformed isothermal TL (PT-ITL) curves.

In a single-aliquot regenerative-dose protocol it is desirable that the signal is completely emptied after each measurement and any sensitivity change must be adequately monitored by the test dose. To satisfy the former requirement we need to heat aliquots to a high temperature in each TL based SAR cycle. For example to date using the 325°C peak one would have to heat to a high temperature such that other overlapping peaks do not contribute to the at 325°C signal during the next measurement. Such high temperature treatment may cause considerable thermally induced sensitivity changes that are not monitored accurately by the test dose. One way of keeping the heat treatment as gentle as possible is by making the measurement at a constant temperature (i.e. isothermally) just below the peak temperature of interest. This would lead to a rapid decay of the signal which would be dominated by the contribution from the TL peak just above the measurement temperature. For example, to stimulate charge from the 325°C peak it is sufficient to hold the sample at 310°C for about 90s, which reduces the signal almost to background level. A good signal separation is expected from the overlapping peaks because the measurement is made at constant temperature. In practice the heating time can be reduced even further as long as the signal is nearly emptied at the end of each cycle. Clearly this is a much less stringent heat treatment than that involved in heating the sample to beyond 500°C. In addition to good signal separation and low sensitivity changes, ITL measurement offers significant advantage in terms of thermal quenching which is constant during the measurement. Moreover, thermal quenching can be reduced by lowering the ITL temperature well below the ramped TL peak temperature, although this also reduces the rate of trap emptying.

Sample K-VII/2B was chosen for investigations of the growth behaviour of the ITL signal. The dose response at different ITL temperatures was measured using a single-aliquot regenerative-dose protocol: a) the natural signal was measured at a given temperature for 500s, b) a test dose and c) an ITL signal measurement at the same temperature as the natural signal. This cycle was then repeated for doses. Measurement different regeneration temperatures for the test dose and the regeneration doses were kept identical to make sure that the same trap has been sampled in both cases. Note that no preheating was used since by definition ITL involves heating the sample until the measurement temperature has been reached. Three aliquots were used for ITL measurement temperatures between 310 to 430°C, using 10°C increment.

Natural ITL signals from different aliquots are plotted for some representative temperatures in Figure 3b. The signals decrease as the stimulation temperature increases and all reach a background level after about 90s of stimulation. All signals show an overall non-exponential decay shape as indicated by data from ITL at 310°C on the log I scale (Figure 3b inset). It is difficult to gain insight into luminescence signal behaviour just by visual examination of a monotonously decaying signal. For a better representation, the ITL signal was converted to a peak shaped form using an arithmetic transformation suggested by Poolton et al. (2003); this transformation is based on a linear increase in the sampling time period. The peak transformed ITL (PT-ITL) signals obtained from isothermal decay curves are much more informative (Figure 3c). Some of the higher temperature PT-ITL curves show evidence for two distinct peaks, suggesting that the non-exponential nature may be caused by contribution to the signal from more than one trap. The peak time of the dominant peak decreases between 310 to 350°C (i.e. the signal decays faster), and then remains more or less constant for higher temperatures. The lack of peak shift above 350°C suggests that these curves represent data from different combinations of traps; otherwise, one would expect the peak time to decrease for higher temperature ITL stimulations.

The integrated signal over the first five seconds of the ITL decay curves was used to derive growth curves for different ITL temperatures. Growth curves were constructed by plotting the ratio between the ITL intensity of the natural or regenerated dose signal (L_x) and the corresponding test dose signal (T_x) , as a function of the given dose. Some representative examples are shown in Figure 4a. For the 310 and 320 °C ITL signals the growth curves fit well to a single saturating exponential function with an average D_0 value of 700 Gy. For measurement temperatures above 320°C, however, the L_x/T_x ratio becomes smaller at given doses > 750 Gy. Also, there is an overall drop in the L_x/T_x values for the stimulation temperatures above 370°C.

The test signal undergoes a dose dependent sensitivity increase as shown in Figure 4b where the sequence of regeneration doses is shown against the cycle number. This increase occurs above 750 Gy dose, and the maximum sensitivity change in the high temperature signal (410°C) is about ten times that in the lower temperature signal (310°C). For the intermediate temperatures it varies systematically. Whether or not this change with dose is reproducible can be tested through repeat dose points. The recycling value for the 1st and 2nd 100 Gy

regeneration doses (SAR cycles 3 and 7) is close to unity for different measurement temperatures (average = 1.06 ± 0.02). However, the recycling value based on the 2nd and the 3rd 100 Gy dose given at the end of SAR (cycle 11) is about unity for 310 °C but then decreases systematically to about 0.4 at higher stimulation temperatures (Figure 4c) (average = 0.63 ± 0.05). In order to check whether the poor recycling is due to changes in the L_x or in the T_x values the data are plotted in Figures 4d and 4 e for the 310 and 390°C ITL signals respectively. It can be seen that both the L_x and T_x signals show a poor recycling, however, the recycling of L_x is much poorer than that of the L_x/T_x ratio. This is perhaps because the T_x corrects for the cumulative sensitivity change prior to the L_x measurement but does not correct for those changes that occur during the measurement of the L_x signal itself. In other words, if the dose dependent sensitivity change seen in Figure 4b occurs before the regeneration ITL (L_x) measurement then it is likely that it will be monitored by T_x . If the change, however, occurs during the L_x measurement and is dependent both on the regeneration dose and the number of repeat measurement (or SAR cycles), then poor recycling values can occur. This is perhaps an explanation for recycling data after a high dose of 750 Gy (cycles 7 and 11 in Figure 4c). A dose dependent sensitivity change occurring due to the L_x measurement implies a dip in the SAR growth curve at high doses; this is because of a large increase in the T_x values for high

Another cause for the dip in the dose response curves at high temperatures may be a dose dependent shift to longer wavelengths in the emission spectra. This hypothesis, however, does not explain the poor recycling values observed in Figure 4c since the shift should be reproducible for a given dose. Therefore, based on the sensitivity change recycling data (Figures 4b and c), we consider that the dominant cause for the dip in the dose response curves may be a dose dependent sensitivity change that occurs during or towards the end of the L_x measurement at temperatures above 320°C during the ITL measurement. This causes the L_x/T_x ratio to decrease as the T_x sensitivity becomes higher than that of L_x .

Two extreme cases referring to the dose response of the 310 and 390°C ITL signals help understand this better (Figures 4d and 4e). If the test dose perfectly monitored the sensitivity of the L_x signal then the shape of the growth curve would only depend on the rate of trapped charge growth. However if the test dose is a function of the given dose and continues to increases linearly with dose, as shown in Figure 4d, then the growth curve will show a reduction in the




Figure 4: a) SAR dose–response curves for some representative ITL measurement temperatures. Three aliquots of the sample K-VII/2B were measured at each temperature. b) Normalised test dose response (with respect to the first value) as a function of SAR cycle or the corresponding regeneration dose (Gy). c) Recycling ratios calculated for the given 100 Gy regeneration doses. Recycling $I = ITL_{cycle} \sqrt{ITL_{cycle}}$ and Recycling $I = ITL_{cy$

 L_x/T_x values as the traps become saturated. In the case of the 310°C ITL signal such a charge saturation limit has not been reached within the given laboratory doses (Figure 4d). Conversely, a reduction in the L_x/T_x values will begin to occur if the test dose sensitivity rises rapidly within the given laboratory dose range. A clear example is the ITL signal at 390°C where a supralinear increase in sensitivity occurs at \geq 450 Gy (Figure 4e). Such an increase causes an apparent dip in the growth curves.

These observations have an important implication for dosimetry. Since dose dependent sensitivity change also occurs at low temperature stimulations, e.g. at 310 and 320°C, although to a much lower magnitude, it is likely that the growth curves for these signals are also significantly distorted at high doses. Thus the real dose saturation level would be even higher than that indicated in the SAR growth curves (Figure 4a). A true saturation level can, however, only be observed if it is possible to measure the L_x signal without causing any sensitivity change. It is important to note that our ability to recycle an L_x/T_x ratio is good even for higher temperatures before a large dose (750 Gy) has been given (Figure 4c). The problem of growth curvature at higher temperatures, therefore, should not affect our ability to estimate D_e as long as the natural dose is below 750 Gy and the natural signal shows a similar dose dependent sensitivity change as that observed in the regeneration signals.

Equivalent doses were calculated for each stimulation temperature by interpolation of the natural to test dose ITL ratio (L_n/T_n) on the growth curves. In most cases, the natural ratio was within the linear region of the growth curves. In Figure 5a each point represents a mean D_e value derived from three aliquots. This is plotted along with the associated standard error, and the dashed curve shows a scaled TL signal from one of the aliquots. The D_e values were about 80 - 100 Gy except for the stimulation temperatures of 350, 360 and 450°C at which they were about 150 Gy

Quartz: Bleaching of the ITL signal

The same aliquots described above were given a dose of 190 Gy and then bleached under the solar simulator (SOL 2) for 1 hour. After bleaching, the residual signal was treated as the natural signal and a two-cycle SAR procedure was carried out using a regenerative-dose of 190 Gy and a test dose of 37 Gy. The ITL growth curve is almost linear in this dose region (Figure 4a). For each aliquot the measurement temperature was the same as that reported in the preceding section. The residual dose for each ITL signal was calculated by interpolating the $L_{\rm n}/T_{\rm n}$ ratio between the origin and the




Figure 5: a) D_e values as a function of ITL measurement temperature for sample K-VII/2B. A scaled TL curve from the sample is also plotted to show the high temperature TL peaks. b) Residual dose after blue light or solar simulator bleaching for ITL signals measured at different temperatures. Same aliquots as those in (a) were used for the assessment of bleaching under these two light conditions. c) Dose recovery on previously unheated aliquots of the sample K-VII/2B as a function of ITL stimulation temperature.

regenerative dose point. Subsequently the same experiment was repeated except that the bleaching was carried out with blue light (470 nm) at room temperature for 1 hour. Again residual $D_{\rm e}$ values were calculated using the two-cycle SAR method as above.

The results are plotted in Figure 5b. For the ITL signal at 310° C the residual D_e after SOL2 bleaching was about 40 Gy. There was an increasing trend to about 100 Gy for higher temperature ITL signals. In the case of blue light bleaching the residual levels were much higher: ~140 Gy for the 310°C ITL signal and up to 180 Gy for higher temperatures. The amount of charge depletion was similar between 350 to 430°C.

Although the signal is measured isothermally in both the cases, the bleaching efficiency is very different for the SOL2 and blue light, especially for ITL signals between 310 and 340°C. One explanation is that the stimulation intensity under the SOL2 simulator is much higher than that under the blue light LED's, which, therefore, leads to greater depletion under the former. Alternatively, it is possible that the increased depletion is mainly due to the shorter wavelength component (< 470 nm) of the SOL2 which leads to an exponential increase in the bleaching rate (Jaek et al., 1999). We consider that the increased short wavelength component from the SOL2 is probably the main cause for increased depletion. If this interpretation is correct then it suggests that the initial ITL signals at 310 and 320°C, which are likely to be derived from the 325°C TL peak, are complex and consist of at least two traps that have similar thermal depths but markedly different optical depths. This causes the two traps to decay at a similar rate during the ITL measurement but one trap is bleachable by visible light and the other only by the short wavelength component of the SOL2 simulator. This multiple trap hypothesis is also supported by very different saturation levels of the 310°C ITL signal and the OSL signal; the latter has been shown to be related to the 325°C peak (Spooner, 1994). The complex nature of the 325°C peak has been previously suggested by Huntley et al. (1996) on the basis of depletion in the TL peak after optical exposure.

Quartz: Dose recovery test

Finally a dose recovery test was carried out on a set of fresh aliquots of sample K-VII/2B. Aliquots were bleached under the SOL2 simulator for two hours. These aliquots were then given a dose of 374 Gy. A four step SAR protocol consisting of regeneration dose, ITL measurement, test dose (50 Gy), and a further ITL measurement was carried out for some

selected temperatures. Three aliquots were used at each ITL measurement temperature. The results are plotted in Figure 5(c). The recovered dose was about 400 Gy for measurement temperatures of 310 and 320°C and then it decreased rapidly down to 175 Gy for 400°C and increased again to 334 Gy for 420°C. A ~15 Gy residual dose for the 310 and 320°C ITL signal determined on separate aliquots after two hours of SOL2 bleaching must also be taken into account. If one considers this residual dose together with the given dose (dashed line in Figure 5c) then dose estimates for the ITL temperatures of 310 and 320°C are in agreement with the known dose in the sample. For higher temperatures the dose estimates are significantly underestimated, especially if one also takes into account the higher residual levels (Figure 5b) superimposed on the given dose.

To confirm the reliability of the dose recovery for the sample under natural solar bleaching conditions, nine aliquots of sample K-VII/2B were bleached under clear daylight (in Denmark) for 1 hour. After bleaching, three aliquots were given a dose of 136 Gy and finally the dose in all nine aliquots was estimated using a four step SAR protocol using a 320°C ITL measurement temperature. The residual dose in the six bleached aliquots was estimated to be 35.0 ± 1.4 Gy, which is similar to that obtained after one hour of SOL2 bleaching (Figure 5b), while that in the three dosed aliquots was 161.7 ± 3.4 Gy. The recovered to given dose (including residual) ratio was calculated to be 0.95 ± 0.04 .

In terms of dosimetry it appears that the 310 and 320°C ITL signals can be used for measuring the dose in quartz up to about 1400 Gy (2 times the D_0 value) in our samples. For higher temperature ITL stimulations (330-350°C), there is a dose dependence in the sensitivity at high regeneration doses (>750 Gy), which causes poor recycling ratios and a dip in the dose response curves. Moreover, these higher temperature ITL signals show poorer bleaching and inaccurate dose recovery. Similar D_e values in Figure 5a for higher temperatures may perhaps be due to a combination of very poor bleaching and dose underestimation (see Figures 5b and 5c).

In the following section we test the ITL dating method on samples from the IG plains, and compare the results with quartz OSL ages, where possible.

Quartz ITL at 320°C – dose measurement on natural samples

Based on the results of our bleaching and dose recovery experiments we estimated D_e in 14 different samples using a four step SAR protocol with the ITL

signal measurement at 320°C. The results are summarized in Table 1.

Quartz OSL ages were found to be comparable with radiocarbon ages (Gibling et al., 2005). Given the good bleaching in the modern sample from the area (Jain et al., 2004) and the good dose recovery in OSL experiments, we consider that quartz OSL D_e values constitute an 'independent dose' record for assessment of the reliability of quartz ITL D_e values. A comparison of OSL and ITL D_e estimates is attempted in Figure 6. Two of the samples are aeolian (triangles), while the remaining are fluvial (circles). Most of the results fall close to a line of unit slope, even at small doses, but two fluvial samples BTH-II/6 and BTH-II/8, surprisingly, have ITL doses smaller than the OSL doses. This causes the regression line to deviate slightly from the line of unit slope (Figure 6). Since we expect that the D_e measured using ITL should be greater than or equal to that measured using OSL, the under-estimation using ITL is probably an artifact. On visual examination it was found that these two samples had a very high concentration of micas; these may give an unstable TL signal (Clark and Sanderson, 1994) and so provide one possible explanation for the age underestimation. The effect of micas on De estimates is however poorly understood and requires further study. Alternatively, it may be possible that the sensitivity correction of the natural signal is not working perfectly for all the samples. The recycling values show that the growth curve is very reproducible and sensitivity change is corrected for appropriately. However, if a major sensitivity change occurs during the first heating i.e. during the measurement of the natural signal then the sensitivity of the subsequent test dose ITL will be different from that of the natural ITL signal. Thus sensitivity change during the first measurement will go unmonitored and cause an offset in the L_n/T_n value. A similar




Figure 6: Comparison between De values derived using OSL and ITL signal at 320°C from quartz in some young samples.

sensitivity change during the readout of the natural OSL signal has been suggested earlier (Stokes and Singhvi, 1999; Jaiswal et al., 2004). Resolving these issues requires further investigation.

In general, the good correlation of the OSL and ITL doses, together with our previous results on dose recovery experiments, implies that the residual ITL in the natural samples, both aeolian and fluvial, were small. It is interesting to note that when close to the OSL saturation dose (~140 Gy), the spread in OSL doses is greater than that in the ITL doses (Figure 6). We consider that present results are encouraging in terms of supporting the accuracy of 320°C ITL dose estimates and their potential use in extending the age range using quartz.

For the seven samples beyond the OSL dating range, it was possible to calculate D_e values using ITL signals measured at 320°C (Table 1). This enabled us to interpret the stratigraphic evolution of one of the key areas, the Kalpi section, in the southern IG plains (Gibling et al., 2005). The maximum D_e value in our samples was 420 Gy (Table 1).

Feldspars


The overall level of agreement between quartz OSL and ITL doses suggests that quartz ITL (at 320°C) can be used as a dosimetric tool at higher doses. With this extension in the independent dose or age record some specific questions that can be put forward are:

- a) How do D_e estimates based on red and blue emission from feldspars compare with those based on quartz ITL?
- b) How does feldspar IRSL (blue emission) compare with the blue/red emission ITL from feldspars?
- c) Does feldspar IRSL (blue emission) for older samples show a similar dose under-estimation as it did in the case of younger samples (Figure 2)?

These questions are addressed below.

Feldspar 310°C ITL (blue emission)

All feldspar ITL measurements were carried out at 310°C to make sure that a thermally stable signal was sampled. These ITL results should be directly comparable with those from IRSL obtained after preheating at 300°C. A slow non-exponential signal decay was observed and a near background level was reached in about 200s (Figure 7a). A four step SAR protocol based on an ITL measurement temperature of 310°C (for 500s) and a test dose of 34 Gy was used for dose estimation. A typical SAR growth curve obtained from these measurements is shown in






Figure 7: a) Blue and red emission ITL decay curves at 310°C measured from sample K-IX/49. The data is plotted on a log ITL scale. b) SAR dose response curves using blue and red ITL at 310°C.

Figure 7b fitted by a single saturating exponential growth curve. An average D_0 value for different samples was 300 Gy and recycling values were within 3% of unity. The maximum D_e value was found to be 305 Gy (sample K-IX/1B), which is well below the saturation range.

Feldspar 310°C ITL (Red emission)

Red TL measurements from feldspars were carried out to make an assessment of fading by comparison with the previously determined D_e values using a) Quartz ITL and b) feldspar blue emission ITL. A broad peak centered at 310°C was observed (Figure 8). The isothermal TL signal at 310°C was found to be about two orders of magnitude smaller than the blue emission signal. The decay shapes, of the two signals were similar (Figure 7a).

The SAR measurement temperature was kept the same as that for the blue emission ITL, i.e. 310°C, in order to sample a geologically stable signal. Again the preheat and cutheat steps were eliminated, and the size of the test dose was 34 Gy. A typical SAR growth curve is shown in Figure 7b which is almost identical to the blue ITL growth curve in the given




Figure 8: Background subtracted red emission TL signal from three aliquots of the sample SNG1 containing natural dose. A heating rate of 2°C/s was used.


dose range. The average D_0 value for different samples was 307 Gy. A close similarity in the dose response characteristics for identical stimulation energy (at 310°C) suggests that the blue and red ITL signals arise from the same trap. The recycling values were generally within 5% of unity suggesting a good sensitivity correction.

The maximum equivalent dose calculated using red ITL was 404 Gy for the second oldest sample K-IX/49. The Red ITL for the oldest sample K-IX/1B was in dose saturation. As seen earlier, the latter was not in dose saturation in the case of IRSL and blue ITL. We attribute this discrepancy to significantly more fading in the IRSL and blue ITL signals than in the red ITL signal, if any. Similarly sample K-V/4 was also found to be in charge saturation

Comparison of feldspar IRSL, blue ITL and red ITL \mathbf{D}_{α}

On average it was observed that D_e values derived from feldspar blue ITL emission are about 18% greater than those derived using IRSL (Figure 9a). Since there appears to be a proportional relationship, except for the oldest sample K-IX/1B, a higher ITL D_e cannot be explained by poorer bleaching of the TL peak prior to deposition. If one ignores the sample, K-IX/1B which lies in the non-linear region of the growth curve, then the dose determined using IRSL is on average 34% lower than that based on blue emission ITL.

The blue ITL doses on the other hand are about 35% smaller than the red ITL D_e values (Figure 9b). As mentioned earlier, the oldest sample K-IX/1B was under charge saturation in red ITL and hence is automatically eliminated from the regression plot. These results imply that IRSL (blue emission) D_e values are on an average about 70% lower than those of the red ITL values.






Figure 9: a) A comparison of D_e values derived using ITL at 310°C with those using IRSL from feldspars. Both the signals have been detected using the blue emission. b) A comparison between D_e values derived using the blue and red ITL signals measured at 310°C.

Comparison of D_ε and ages from Quartz and Feldspar

All feldspar IRSL De values derived previously are plotted against the corresponding quartz OSL and ITL doses in Figure 10a. The regression line indicates that feldspar D_e values are only 23% lower than those from quartz. In contrast, we had inferred that feldspar IRSL doses were about 40% lower than quartz ITL doses on the basis of D_e results from the younger samples (Figure 2). This result is contrary to our expectation since the total amount of fading should be even greater in older samples as the natural signal occurs in the more non-linear part of the growth curve. Therefore, one would expect the average dose under-estimation to increase when older samples are also considered. This dose comparison suggests that the correction factor derived from young samples cannot be simply extrapolated to the old samples.

The D_e values based on blue ITL of feldspars are similar to those from ITL of quartz except for the oldest sample K-IX/1B which forms an outlier to the general trend (Figure 10b). The datapoints generally fall on a line of slope 1. However the dose in feldspars should be higher than that in quartz because of an additional internal dose rate. The y=x trend observed here, therefore, suggests significant fading in blue emission ITL signal from feldspars.

The red ITL D_e values are on an average about 50% greater than those of quartz. However, there is a large scatter at high doses (Figure 10c). Perhaps this is because these high red ITL D_e values are well beyond the D_0 value of 307 Gy. In quartz it is generally possible to measure dose accurately until about 15% of the saturation level but we are not aware of such saturation constraints on dose estimates in feldspar luminescence. If one ignores the red ITL doses above 330 Gy in the regression plot then feldspar red emission ITL doses are about 37% higher than corresponding doses in quartz.

To check if feldspar red ITL and quartz ITL ages are comparable the internal dose rate in feldspar was calculated based on 12 ± 0.5 % K and 400 ± 100 ppm Rb for a grain size of 100 µm (Table 1). This contributed an additional dose rate of 0.4 ± 0.02 Gy/ka to feldspars. Our calculation assumed that observed red ITL comes mainly from K-feldspars. Quartz and feldspar ages for the same samples are plotted in Figure 10d. There is a tendency for feldspar ages to be higher than quartz ages. However, except for four samples the data is consistent with a y=x relationship within 1σ errors, and if 2σ errors are considered then there is only one outlier to this trend. In none of the samples is a dose under-estimation in feldspars observed. If the internal feldspar dose rate is an over-estimate, then the offset between quartz and feldspar ages will be even greater than that seen in Figure 10d.

It may appear that the trend observed in Figure 10d is largely due to an absence of fading. However, a tendency to over-estimate the age using the red emission ITL from feldspars suggests that there may be an additional factor influencing the age calculation. It may be possible that there is a sensitivity change during the natural red ITL measurement which causes an increase in L_n/T_n ratio. Such a sensitivity change either does not occur in blue ITL measurements because of a different recombination centre, or the change does occur but it is not apparent due to the presence of significant fading in the blue signal. Future investigations should clarify if sensitivity change during red ITL measurements are significant or not.




Figure 10: a) A comparison between D_e values derived using IRSL from feldspars, and OSL and 320°C ITL signals from quartz. b) A comparison between D_e values derived using blue emission ITL at 310°C from feldspars and UV emission ITL at 320°C from quartz. c) A comparison between D_e values derived using red emission ITL at 310°C from feldspars and UV emission ITL at 320°C from quartz. d) A comparison between feldspar red ITL and quartz ITL ages (same D_e data as (c)).

Conclusions

The following conclusions can be made with respect to our samples from the Indo-Gangetic plains:

- 1. Isothermal TL signals in quartz at 310 and 320 °C offer an approach to increase the dating range. The maximum measurable D_e value using these signals is about 1.4 kGy. This is an order of magnitude increase in measurable dose as compared to quartz OSL which saturates at about 150 Gy in our samples.
- 2. Dose saturation levels and the bleaching data using blue or SOL2 light suggest that quartz ITL at 310 and 320°C (and therefore the 325°C TL peak) consists of traps which have similar thermal depths but significantly greater optical depths than the fast component OSL trap. Therefore there is a possibility to sample these traps using a stimulation energy

higher than that of blue light (2.6 eV) to extend the age range using an OSL method.

- 3. Feldspar IRSL (blue emission) may show a greater dose under-estimation than the blue emission ITL signal measured at 310°C.
- 4. The red emission ITL in feldspars probably suffers from sensitivity change during the measurement of the natural signal. Therefore a firm conclusion regarding fading in this signal cannot be made at present.
- 5. The average D_0 value (saturation characteristic) calculated from SAR dose response curves on different samples is smallest for quartz OSL (~65 Gy) followed by feldspar IRSL (~173 Gy). Feldspar red and blue ITL signals at 310°C measurement temperature show similar D_0 values of ~303 and

 $\sim \! \! 307$ Gy respectively. Quartz UV ITL shows the highest saturation level as indicated by an average D_0 value of 700 Gy.

- 6. In feldspars the red and blue ITL signals measured at 310°C probably arise from the same trap. This is deduced from their similar dose response when measured using an identical stimulation energy (ITL at 310°C). The differences in D_e values obtained using these signals may, therefore, be caused by the fading of charge in the recombination centre and/or changes in recombination probability during the first heating for measurement of the natural signal. The latter may cause a sensitivity change that is not monitored by the natural test dose signal $(T_{\rm n})$.
- 7. Because of a lower dose rate and a higher saturation level (compared to feldspars) quartz ITL offers the best possibility to extend the luminescence dating range in samples from the southern Indo-Gangetic plains.

Future scope of this work

Our preliminary investigations reported here give important support for the use of TL signal in quartz to extend luminescence dating beyond the OSL range. There are several important questions raised or data unexplained which require future detailed investigations. These include:

- 1) What is the composition of the high temperature TL signals in quartz? Interpretation of the OSL signal as the 325°C peak appears to be a gross over simplification, although, it is not ruled out that the OSL signal may have a similar thermal depth as the 325°C peak. Our data on dose response and bleaching behaviour suggests more than one traps, in the 310-320°C ITL curves, that have different optical depths and dose saturation characteristics. A clear understanding of the kinetics of these TL signals and of thermally induced sensitivity changes during signal measurement will be important for developing widely applicable dosimetric techniques for extending the age range.
- 2) For widespread application of ITL SAR procedure to both quartz and feldspars, it is important to understand the nature of sensitivity change, if any, during the first measurement. This is especially important for the red TL signal from feldspars.
- 3) We speculate that dose dependent sensitivity change at high doses may cause an artificial curvature in the quartz ITL growth curves; this is because we expect such a sensitivity change to occur because of the L_x measurement. If this sensitivity change is associated with the recombination process

and continues to occur as a function of dose at high doses, then a dip in the growth curves is expected once the trapped charge becomes saturated after a certain dose. Thus there is a balance between trapped charge growth and recombination related sensitivity change. Although this behaviour may not have any bearing on the accuracy of dose estimates as long as natural doses are below the curve maxima (assuming that similar dose dependent sensitivity change occurs for the natural signal), or on the reproducibility of the growth curve (recycling point), it can severely limit our ability to measure high doses because of an apparent early saturation. A better understanding of dose dependent sensitivity changes and such effects requires future investigations. It is likely that such effects can also be significant in quartz OSL.

- 4) A better understanding of poor reproducibility in the dose response of high temperature ITL signals (>320°C) can be useful for exploiting the dosimetric potential of these signals using SAR.
- 5) Our preliminary data from feldspars suggests that both blue and red emission ITL signals at 310°C use the same trap. Further investigations are required to confirm this.

Acknowledgements

We thank Prof. A.K. Singhvi, Prof M.D. Sastry and P. Morthekai for helpful comments and a constructive review of this paper. S. Huot is thanked for calculation of internal dose rate in feldspar.

References

- Aitken, M. J. (1985). *Thermoluminescence Dating*. Academic Press.
- Bøtter-Jensen, L., Bulur, E., Murray, A.S. and Poolton, N.R.J. (2002). Enhancements in luminescence measurement techniques. *Radiation Protection Dosimetry* **101**, 119-124.
- Clark, R.J. and Sanderson, D.C.W. (1994). Photostimulated luminescence excitation spectroscopy of feldspars and micas. *Radiation Measurements* **23**, 641 646.
- Fattahi, M. and Stokes, S. (2000). Extending the time range of luminescence dating using red TL (RTL) from volcanic quartz. *Radiation Measurements* **32**, 479-485.
- Fattahi, M. and Stokes, S. (2003). Red luminescence from potassium feldspar for dating applications: a study of some properties relevant for dating. *Radiation Measurements* **37**, 647-660.

Franklin, A.D. and Hornyak, W. F. (1990). Isolation of the rapidly bleaching peak in quartz TL glow curves. *Ancient TL* **8**, 29-31.

- Gibling, M.R., Tandon, S.K., Sinha, R. and Jain, M. (2005). Discontinuity-bounded alluvial sequences of the southern Gangetic plains, India: aggradation and degradation in response to monsoonal strength. *Journal Sedimentary Research* 75, 369-385.
- Huntley, D.J. and Lamothe, M. (2001). Ubiquity of anomalous fading in K—feldspars and the measurement and correction for it in optical dating. *Canadian Journal of Earth Science* **38**, 1093–1106.
- Huntley, D.J., Short, M.A. and Dunphy, K. (1996). Deep traps in quartz and their use for optical dating. *Canadian Journal of Physics* **74**, 81-91.
- Huntley, D. J. and Prescott, J. R. (2001). Improved methodology and new thermoluminescence ages for the dune sequence in south-east South Australia. *Quaternary Science Reviews* **20**, 687-699
- Jaek, I., Hütt, G. and Streltsov A. (1999). A study of deep traps in alkali feldspars and quartz by optically stimulated afterglow. *Radiation Protection Dosimetry* 84, 467-470.
- Jain, M., Murray, A.S. and Bøtter-Jensen, L. (2004). Optically stimulated luminescence dating - how significant is incomplete light exposure in fluvial environments? *Quaternaire* 15, 143-157.
- Jain, M., Tandon, S.K., Singhvi, A.K., Mishra, S. and Bhatt, S.C. (2005). Quaternary alluvial stratigraphic development in a desert setting: a case study from Luni river basin, Western India. In Fluvial Sedimentology VII, Eds. M. Blum and S. Marriott, Special Publication of International Association of Sedimentologists 35, 349-371.
- Jaiswal, M.K., Jain, V., Wasson, R.J., Juyal, N. and Singhvi, A.K. (2004). Luminescence characteristics of fluvial sediments from complex lithologies in Himalaya: Implications for SAR and provenance. Abstract UK luminescence and ESR meeting (September 5-8), University of St. Andrews, Scotland.
- Murray, A.S. and Olley, J.M. (2002). Precision and accuracy in the optically stimulated luminescence dating of sedimentary quartz: a status review. *Geochronometria* **21**, 1-16.
- Murray, A.S. and Wintle, A.G. (2000a). Application of the single-aliquot regenerative-dose protocol to the 375°C quartz TL signal. *Radiation Measurements* **32**, 579-583.
- Murray, A.S. and Wintle, A.G. (2000b). Luminescence dating of quartz using an improved single aliquot regenerative dose protocol. *Radiation Measurements* **32**, 57-73.

Murray A.S., Marten, R., Johnston A. and Marten P. (1987). Analysis for naturally occurring radionuclides at environmental concentrations by gamma spectrometry, *Journal of Radioanalytical and Nuclear Chemistry* **115**, 263–288.

- Poolton, N. R. J., Bøtter-Jensen, L., Andersen, C. E., Jain, M., Murray, A.S., Malins, A.E.R. and Quinn, F.M. (2003). Measuring modulated luminescence using non-modulated stimulation: ramping the sample period. *Radiation Measurements* 37, 639-645.
- Singarayer, J.S. and Bailey, R.M. (2003). Further investigations of the quartz optically stimulated luminescence components using linear modulation. *Radiation Measurements* 37, 451-458.
- Spooner, N. A. (1994). On the optical dating signal from quartz. *Radiation Measurements* **23**, 593-600
- Stokes, S. and Singhvi A.K. (1999). Personal communication.
- Wallinga, J., Murray A.S., Duller, G.A.T. and Törnqvist, T.E. (2001). Testing optically stimulated luminescence dating of sand-sized quartz and feldspar from fluvial deposits. *Earth and Planetary Science Letters* **193**, 617-630.
- Zink A.J.C. and Visocekas, R. (1997). Datability of sanidine feldspars using the near-infrared TL emission. *Radiation Measurements* **27**, 251–261.

Reviewer

Ashok Singhvi

Comments

This is an important paper with potential for older samples and should generate a lot of interest in the dating community. I also expect that the authors and others will follow up in detail as some of the observations need further probing. At present the observations intrigue me as much as they enthuse me to explore them further.